

## Filter container "AQUA GUARD - AFM®-FILTER"

A guarantee for clean water and low operating costs. BEHNCKE filter containers. Made in Germany.

The filtering technology is the most important component in the treatment of swimming pool water. BEHNCKE's special filter operating technology not only reduces the energy and water consumption, it also lowers the consumption of chemicals. In addition to the economic aspects related to reduced operating costs, it also makes an important ecological contribution. A clever investment for our future!

**BEHNCKE filter container "AQUA GUARD - AFM®-FILTER" - a high quality standard with optimal operating reliability and excellent benefit-cost ratio.**

- High-quality thanks to its fiberglass reinforced polyester resin with inner sealing
- Large service opening (ø 8.7") with an acrylic transparent cover
- Built-in 6-way and 12-way laterals
- Drain with a 3/4" female thread
- Pressure gauge and manual air bleeder
- Max. working temperature 108°F, working pressure 29 psi
- Connection with adapter to slip
- Optionally also available in ozone-resistant material



**AFM® - The unique bio-resistant activated filter media!**

### What is AFM®?

AFM® (Activated Filter Media) is a modern filter medium that replaces the filter sand in pressure and gravity sand filters. In comparison to even high-quality filter sand, AFM® has significantly better application properties.

Changing over from sand to AFM® leads to a considerable increase in the performance of your filtration system. AFM® is manufactured by Dryden Aqua from conditioned glass and also makes a valuable contribution to environmental sustainability.

**AFM® is successfully working in over 100'000 private and public swimming pools worldwide.**



### Filter container "AQUA GUARD - AFM®-FILTER" - Technical specifications

Size x Height	Ø 19.7" x 36.2"	Ø 23.6" x 39.4"	Ø 31.5" x 44.5"
Outer diameter	Ø 20.5"	Ø 24.4"	Ø 32.3"
Connection*	2" slip	2" slip	2" slip
Filter area	2.0 ft <sup>2</sup>	2.9 ft <sup>2</sup>	5.2 ft <sup>2</sup>
Weight (approx.)	35 lb.	46 lb.	101 lb.
AFM® Grade 1 (0.4–1.0)	184 lb. / 4bags	322 lb./ 7 bags	598 lb. / 13bags

\* Adapter to slip included